


**726.402**







- Fabricado em aço inoxidável AISI304 ou AISI316
- Material (EN): EN 1.4301
- Pavimento: betão ou azulejo

**RALO DE PAVIMENTO COM DESCARGA HORIZONTAL, 200 x 200 mm**




Referência	D [ mm ]	D1 [ mm ]	F [ mm ]	H [ mm ]	H1 [ mm ]	W1 [ mm ]
726.402.075	75	160	200 x 200	170	137	250
726.402.110	110	160	200 x 200	170	118	153

**GRELHAS COMPATÍVEIS**




Ranhurada	Entramada	Rebaixada	Hygienic Pro	Ladder	Duche	3MM
790.168.000.10	790.168.000.22	790.168.000.06	790.168.000.60	790.168.000.28	790.168.000.04	790.168.000.03
R50 (5000 Kg.)	R50 (5000 Kg.)	L15 (1500 Kg.)	R50 (7000 Kg.)	M125 (12000 Kg.)	K3 (800 Kg.)	L15 (1750 Kg.)

**SIFÃO REMOVÍVEL**



Referência	D [ mm ]	H [ mm ]	S [ mm ]	D2 [ mm ]	Caudal [ l/seg ]
562.002.000 S	157	115	52	107	3,3

**CESTO DE RETENÇÃO DE INERTES**



Referência	H [ mm ]	D2 [ mm ]	Volume [ l ]
780.002.001.05	22	150	0,2