


763.401








- Fabricado em aço inoxidável AISI304 ou AISI316
- Material (EN): EN 1.4301
- Pavimento: betão ou azulejo

## RALO DE PAVIMENTO COM DESCARGA HORIZONTAL, 250 x 250 mm




Referência	D [ mm ]	D1 [ mm ]	F [ mm ]	H [ mm ]	H1 [ mm ]	W1 [ mm ]
763.401.110	110	160	250 x 250	221	169	153

## GRELHAS COMPATÍVEIS




Ranhurada	Entramada	Rebaixada	Hygienic Pro	Ladder	Duche	3MM
790.218.000.10	790.218.000.22	790.218.000.06	790.218.000.60	790.218.000.28	790.218.000.04	790.218.000.03
R50 (5000 Kg.)	L15 (1250 Kg.)	L15 (1000 Kg.)	A15 (4000 Kg.)	R50 (6000 Kg.)	K3 (700 Kg.)	L15 (1500 Kg.)

## SIFÃO REMOVÍVEL



Referência	D [ mm ]	H [ mm ]	S [ mm ]	D2 [ mm ]	Caudal [ l/seg ]
562.002.000 S	157	115	52	107	3,3

## CESTO DE RETENÇÃO DE INERTES



Referência	D1 [ mm ]	H [ mm ]	D2 [ mm ]	Volume [ l ]
780.002.000.05	140	74	155	0,9