


**766.503**






- Fabricado em aço inoxidável AISI304 ou AISI316
- Material (EN): EN 1.4301
- Pavimento: resina

## RALO DE PAVIMENTO COM DESCARGA VERTICAL, GRELHA Ø305




Referência	D [ mm ]	D1 [ mm ]	F [ mm ]	H [ mm ]	H1 [ mm ]
766.503.075	75	250	Ø305	269	65
766.503.110	110	250	Ø305	278	76
766.503.160	160	250	Ø305	296	95

## GRELHAS COMPATÍVEIS





Ranhurada	Entramada	Rebaixada	Hygienic Pro	Ladder	3MM
790.273.000.10 S	790.273.000.22	790.273.000.06	790.273.000.60	790.273.000.28	790.273.000.03 S
M125 (8333 Kg.)	L15 (2000 Kg.)	K3 (750 Kg.)	R50 (5000 Kg.)	M125 (10000 Kg.)	L15 (1000 Kg.)

## SIFÃO REMOVÍVEL



Referência	D [ mm ]	H [ mm ]	S [ mm ]	D2 [ mm ]	Caudal [ l/seg ]
562.103.000 S	246	118	52	197	7,8

## CESTO DE RETENÇÃO DE INERTES



Referência	D1 [ mm ]	H [ mm ]	D2 [ mm ]	Volume [ l ]
780.004.020.05	220	125	245	3,9
780.004.010.05	-	41	245	0,8