


TYPE 150.000


- Fabricado em aço inoxidável AISI304 ou AISI316
- Material (EN): EN 1.4301
- Pavimento: betão ou azulejo

CORPO DE RALO COM DESCARGA VERTICAL










Referência	D [mm]	D1 [mm]	H [mm]	H1 [mm]	D2 [mm]
150.000.075	75	140	173	63	113
150.000.110	110	140	141	79	113

SECÇÃO SUPERIOR 200 X 200 mm



Referência	D [mm]	F [mm]	H [mm]	H5 [mm]
710.402.000	110	200x200	100	51


GRELHAS COMPATIVAS



Ranhurada	Entramada	Rebaixada	Hygienic Pro	Ladder	Duche	3MM
790.168.000.10	790.168.000.22	790.168.000.06	790.168.000.60	790.168.000.28	790.168.000.04	790.168.000.03
R50 (5000 Kg.)	R50 (5000 Kg.)	L15 (1500 Kg.)	R50 (7000 Kg.)	M125 (12000 Kg.)	K3 (800 Kg.)	L15 (1750 Kg.)


TYPE 150.000

SIFÃO REMOVÍVEL



Referência	D [mm]	H [mm]	S [mm]	D2 [mm]	Caudal Máximo [l/seg]
502.050.110	108	89	50	85	1,7

CESTO DE RETENÇÃO DE INERTES



Referência	H5 [mm]	D2 [mm]
502.000.000 S	22	150