


760.603


- Fabricado em aço inoxidável AISI304 ou AISI316
- Material (EN): EN 1.4301
- Pavimento: vinil

RALO DE PAVIMENTO COM DESCARGA VERTICAL, GRELHA Ø305



Referência	D [mm]	D1 [mm]	F [mm]	Z [mm]	H [mm]	H1 [mm]
760.603.110	110	250	Ø332	Ø375	366	76

GRELHAS COMPATÍVEIS




Ranhurada	Entramada	Rebaixada	Hygienic Pro	Ladder	3MM
790.273.000.10 S	790.273.000.22	790.273.000.06	790.273.000.60	790.273.000.28	790.273.000.03 S
M125 (8333 Kg.)	L15 (2000 Kg.)	K3 (750 Kg.)	R50 (5000 Kg.)	M125 (10000 Kg.)	L15 (1000 Kg.)

SIFÃO REMOVÍVEL



Referência	D [mm]	H [mm]	S [mm]	D2 [mm]	Caudal [l/seg]
562.103.000 S	246	118	52	197	7,8

CESTO DE RETENÇÃO DE INERTES



Referência	D1 [mm]	H [mm]	D2 [mm]	Volume [l]
780.004.020.05	220	125	245	3,9
780.004.010.05	-	41	245	0,8